62289 - TF1 Omega Filter Flushing Adapter

The Fernox TF1 Omega Filter Flushing Adapter quickly and easily connects a Fernox Powerflow Flushing Machine to the heating system via a Fernox TF1 Omega Filter. It is fitted by simply replacing the filter body with the adapter.

- Fast, easy flushing with connection via the Fernox TF1 Omega Filter
- Enables the full flow rate to optimise cleaning efficiency
- Allows the primary side of the secondary heat exchanger on combination boiler to be cleaned by simply turning on the domestic hot water tap to engage the boiler diverter valve
- Fernox TF1 Omega Filter Flushing Adapter is rated to 85°C

Application

1. Drain the central heating system water.
2. Replace the TF1 Omega Filter body with the TF1 Omega Filter Flushing Adapter.
3. Connect the Fernox Powerflow Flushing Machine to the TF1 Omega Filter Flushing Adapter. Use 3/4” BSP female nut liner and seals, as provided with the Fernox Powerflow Flushing Machine.

Packaging, Handling & Safety

Individually packaged with instructions included. No special storage requirements.

Specification

When used appropriately, the Fernox TF1 Omega Filter Flushing Adapter is maintenance free.

Volumetrics & Barcodes

Barcode EAN	5014551622890	OCU Barcode	

Copyright Fernox © 2026

Single Unit Weight (kg)	0.56	Outer Carton Weight (kg)	9.1
Single Unit Height (mm)	80	Outer Carton Height (mm)	152
Single Unit Width (mm)	100	Outer Carton Width (mm)	273
Single Unit Depth (mm)	80	Outer Carton Depth (mm)	195

Last Modified	2026-10-01T08:31:21.474000

Copyright Fernox © 2026