62553 - Electrolytic Scale Reducer 3/4" Threaded

The Fernox Electrolytic Scale Reducer range uses electrolytic principles to prevent the build-up of scale throughout the home, and remains effective for up to 10 years, dependent on water usage. It works by altering the structure of the hardness salts, inducing coagulation and providing benefits to a range of appliances from kettles to showers and boilers offering whole house protection against scale. Part L of the Building Regulations (England and Wales) states that in hard water areas which exceed 200ppm, provision should be made to treat feed water to water heaters and hot water circuits of combination boilers to reduce the rate of limescale formation as well as limiting its harmful effects on energy efficiency

- An in-line scale reducer to prevent the build-up of scale using electrolytic principles
- Whole house protection
- A brass, nickel plated unit
- No maintenance
- Lasts for up to 10 years
- WRAS approved product

Application

The Fernox Electrolytic Scale Reducer is installed into the pipework. In an average domestic usage household the Fernox Electrolytic Scale Reducer will provide whole house protection for approximately ten years dependent on water usage levels. The unit is effective immediately and is guaranteed for 12 months against manufacturing defects. The unit is pressure rated to 10 bar at 20˚C with an operating temperature of 2˚C to 40˚C (cold feed) and is designed for 3/4" pipework. Install in compliance with WRAS installation requirements IRN R001, R120, R150, R170, R290 and/or local water regulations

Packaging, Handling & Safety

The Fernox Electrolytic Scale Reducer can be installed in horizontal or vertical pipework. The unit is classified as non-hazardous.

Specification

Material: Forged Brass, Nickel Plated

Copyright Fernox © 2026

Volumetrics & Barcodes

Barcode EAN	5014551625532	OCU Barcode	05014551002395
Single Unit Weight (kg)	0.6	Outer Carton Weight (kg)	7.23
Single Unit Height (mm)	40	Outer Carton Height (mm)	90
Single Unit Width (mm)	185	Outer Carton Width (mm)	221
Single Unit Depth (mm)	40	Outer Carton Depth (mm)	200

Last Modified	2026-10-01T08:31:21.474000

Copyright Fernox © 2026